



TECHNICAL DATA SHEET  
V012020

# XTRA 5W30 C3

## DESCRIPTION

Universal fuel economy synthetic engine oil formulated from the latest generation additives.

## APPLICATION

**Bardahl XTRA 5w30 C3** is an "universal" lubricant. It is formulated from a low-viscosity high-performance Mid S.A.P.S technology, developed for petrol and diesel passenger car and duty vehicle engines, with extended drain interval. It helps extend the lifespan of 3-way catalytic converters and DPF. Suitable for the Longlife III (VW) program.

## SPECIFICATIONS

This product offers the following performance level:

|               |                      |
|---------------|----------------------|
| ACEA          | C3                   |
| API           | SN                   |
| VW            | 504.00 / 507.00      |
| MERCEDES-BENZ | MB 229.31/ MB 229.51 |
| PORSCHE       | C30                  |
| BMW           | Longlife-04          |

## PROPERTIES

- ✓ Helps limiting the fuel overconsumption,
- ✓ Helps limiting polluting emissions,
- ✓ Is suitable for modern catalytic converters,
- ✓ Forms a lubricating film protecting the engine at high temperature,
- ✓ Extends the drain intervals,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Provides a high protection against corrosion, wear and the formation of foam.

**SADAPS BARD AHL ADDITIVES & LUBRICANTS**

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)



## TECHNICAL DATA SHEET V012020

### TECHNICAL DATA

|                        |         |       |
|------------------------|---------|-------|
| Density at 15°C        | Kg/l    | 0,855 |
| Viscosity at -35°C     | mPa.s   | 6120  |
| Viscosity at 40°C      | mm2/s   | 71    |
| Viscosity at 100°C     | mm2/s   | 12,10 |
| Viscosity Index        |         | 169   |
| Flash point COC, °C    | °C      | 228   |
| Pour point, °C         | °C      | -39   |
| TBN Alkalinity         | mgKOH/g | 7,7   |
| Sulphated Ash contents | %       | 0,73  |

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

### RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

### REFERENCES & AVAILABILITIES

|       |         |
|-------|---------|
| 34103 | 3 x 5 L |
| 34107 | 205 L   |

#### SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI  
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - [www.bardahlfrance.com](http://www.bardahlfrance.com)