



XTRA 5W30

DESCRIPTION

Universal synthetic lubricant for petrol and diesel engines (equipped or not with a DPF, turbo-charged or not).

APPLICATION

BARDAHL XTRA 5w30 is formulated from a Mid S.A.P.S technology for an optimal cleaning. Suitable for petrol or diesel engines equipped with a 3-way catalytic converter and a DPF.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C2, C3
API	SN
VW	505.01
MERCEDES-BENZ	MB 229.51 / 229.52
GM-OPEL	DEXOS 2
BMW	Longlife-04

PROPERTIES

- ✓ Helps limiting combustion ashes,
- ✓ Forms a lubricating film protecting the engine at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Provides a high protection against corrosion, wear and the formation of foam.



TECHNICAL DATA

Density at 15°C	Kg/l	0,848
Viscosity at -30°C	mPa.s	6000
Viscosity at 40°C	mm ² /s	69,09
Viscosity at 100°C	mm ² /s	11,35
Viscosity Index		160
HSTS Viscosity	mPa.s	3,6
Flash point COC, °C	°C	242
Pour point, °C	°C	-36
TBN Alcalinity	mgKOH/g	7,8
Sulphated Ash contents	%	0,77

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

34111	12 x 1 L
34112	4 x 4 L
34113	3 x 5 L
34117	205 L