

TECHNICAL DATA SHEET V012020

XTRA 5W40

DESCRIPTION

Universal synthetic lubricant for petrol and diesel engines (equipped or not with a DPF, turbocharged or not).

APPLICATION

Bardahl XTRA 5w40 is formulated from a Mid S.A.P.S technology for an optimal cleaning. Suitable for petrol or diesel engines equipped with a 3-way catalytic converter and a DPF.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C3
API	SN
VW	505.01
MERCEDES-BENZ	MB 229.51
BMW	Longlife-04

PROPERTIES

- √ Helps limiting combustion ashes,
- ✓ Forms a lubricating film protecting the engine at high temperature,
- √ Offers excellent dispersion and detergency properties,
- √ Makes cold starting easier,
- ✓ Provides a high protection against corrosion, wear and the formation of foam.



TECHNICAL DATA SHEET V012020

TECHNICAL DATA

Density at 15°C	Kg/I	0,847
Viscosity at -35°C	mPa.s	6460
Viscosity at 40°C	mm2/s	83,00
Viscosity at 100°C	mm2/s	13,40
Viscosity Index		164
Flash point COC, °C	°C	236
Pour point, °C	°C	-30
TBN Alcalinity	mgKOH/g	7,8
Sulphated Ash contents	%	0,77

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

<u>Handling</u>: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

<u>Storage</u>: it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

34123	3 x 5 L
34127	205 L