

ATF 8HP

DESCRIPTION

High quality synthetic automatic transmission fluid with low viscosity for a more responsive transmission. Suitable for automatic transmissions.

APPLICATION

BARDAHL ATF 8 HP has excellent stability and fluidity at low temperatures. Ideal for cold starts. The **ATF 8HP** can be used in many automatic transmissions and has been formulated for the lubrication of ZF 8HP (8HP45, 8HP55, 8HP70, 8HP90 ...) transmissions as it has a strong fuel economy contribution. It can also be used for some 6HP (VAG, BMW models).

SPECIFICATIONS

This product meets the following performance levels:

AISIN WARNER	JWS 3309 (T-IV), JWS 3317, JWS 3324 (WS), JWS AW-1
ALISON	C-4 TES-228
BMW/MINI	7045E BMW/MINI 83 22 0 402 413/ LA 2634, ZF 5 HP 30
	LT71141 (ZF 5 HP 18FL/19FL/24A), ETL 8072B, JWS 3309 (T-IV) ZF 5 HP 30
BENTLEY	PY112995PA
BOSCH	TE-ML 09
CHRYSLER	ATF+, ATF+2, ATF+3, ATF+4, JWS 3309, MOPAR AS 69 RC (T-IV), MS-7176E, MS-9602, P/N 05127382AA
DAEWOO	LT71141
DAIHATSU	Alumix ATF Multi, Ammix ATF D-II, Ammix ATF D-III SP
FIAT	9.55550-AG1, 9.55550-AG2, 9.55550-AV1, 9.55550-AV4, JWS 3309 T-IV
FORD	EAP -M2C166H, FNR5, JWS 3309, M2C138-CJ, M2C166-H, M2C202-B, M2C919-E, M2C922-A1 Ford M2C924-A (XT-8-QAW), Mercon, Mercon V, XL-12, XT-2-QDX (M), XT-2-QSM (S)
FUSO	ATF-A4, ATF-SPIII
GM DEXRON	1940700, 21005966 (Transaxle), 22717466, 88900925, 93160393, 9986195 (Aisin AW, JWS 3309), 9986195 (Aisin AW, JWS 3309), Dexron II, II D, II E III G, Dexron III H, TASA
Hino Blue Ribon	ATF
HONDA	Z-1 (except in CVT)
HYUNDAI/KIA	DW-1, Dex-II, JWS 3314, NWS-9638, SP-II, SP-III (except in CVT's), SP-IV, SP-IV M, SP-IV RR
IDEMITSU	K17 3100 PL085
ISUZU	Besco 08200-9001, Besco ATF SP, Besco ATF-II, Besco ATF-III, Besco SCS Fluid
JASO	M315 Type 1A, M315 Type 1A LV, M315 Type 2A
JAGUAR LAND ROVER	ATF 3403 M115, ATF LT71141 (ZF 5HP24), Fluid 8432, JLM 20238



JEEP	ATF +3
LAND ROVER	LR0234288, TYK500050
MAN	339 Type V1, 339 Type V2, 339 Type Z1, 339 Type Z2, 339 Type Z3
MB	236.10, 236.9 (DTFR 13C170)
MAZDA	ATF 3317, ATF D-II, ATF F-1, ATF FZ, ATF M-III, ATF M-V, ATF N-1, ATF S-1
MITSUBISHI	Diaqueen ATF PA, Diaqueen AW, Diaqueen J2, Diaqueen J3, Diaqueen SK, Diaqueen SP-II, Diaqueen SP-III (except in CVT's)
NISSAN	Matic C, Matic D, Matic Fluid S, Matic J, Matic K
PSA	9730.AE (AL4 automatic gearbox), JWS 3309, LT 71141, LT71141 (ZF 5HP19FL, 5HP20), S71 2340, Z 000169756, ZF 4HP20
PORSCHE	ATF 3403-M115, LT71141 (ZF 5HP19FL, 5HP20), P/N 000 043 205 09, P/N 000 043 205 28, P/N 999 917 547 00, T-IV (JWS 3309), Z 000169756
RENAULT	DPO/AL4, Samsung SATF-D
SAAB	P/N 93 165 147, T-IV (JWS 3309)
SATURN	T-IV (JWS 3309)
SCION	ALL VEHICLES
SUBARU	ATF, ATF-5AT, ATF-H, Dexron II, K0140Y0700
SUZUKI	AT OIL 5D06, ATF 2326, ATF 2384K, ATF 3309, ATF 3314, ATF 3317, ATF AW-1
TOYOTA	ATF D-III, ATF DII, ATF T—IV, ATF T-III, ATF WS including Toyota hybrid system, D-II, T-I, T-II, T-III, T-IV
VAG	LT 71141 (ZF 5HP 18FL/19FL/24A), VW G 052 025, VW G 052 055, VW G 052 162 (ZF LifeguardFluid 5), VW G 052 990, VW G 055 005 (ZF LifeguardFluid 6), VW G 055 025 (JWS 3309), VW G 055 540, VW G 060 162 (ZF LifeguardFluid 8), VW G US 000 162, VW TL 521 62
VOITH	H55.6335.xx (60.000km)
VOLVO	97325, 97335, P/N 1161540
ZF	4HP20/AL4, 6HP, 8HP, TE-ML 03D, TE-ML 04D, TE-ML 09, TE-ML 11A, TE-ML 11B, TE-ML 14A, TE-ML 14B, TE-ML 16L, TE-ML 17C

PROPERTIES

- ✓ **High viscosity index** ensuring good stability,
- ✓ Longer lifespan,
- ✓ **Very low pour point**,
- ✓ Very good thermal stability and anti-oxidation protection,
- ✓ Anti-wear, anti-corrosion and anti-foam,
- ✓ High-performance anti-friction additives,
- ✓ Inert for seals and non-ferrous metals,
- ✓ Good resistance to vibrations,
- ✓ Quick commissioning during cold starts,
- ✓ Viscosity to avoid overconsumption (fuel economy),
- ✓ **Red color.**



TECHNICAL DATA

Density at 15°C	Kg/l	0,843
Viscosity 40°C	mm ² /s	29,53
Viscosity 100°C	mm ² /s	5,83
Viscosity Index		155
Flash point COC, °C	°C	>200
Pour point, °C	°C	-42

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: All safety information on the handling and use of this product is provided in the Material Safety Data Sheet. Always check the manufacturer car manual before use.

Storage: it is recommended to use the product within 60 months. It must be stored in the original sealed packaging, protected from light, moisture and excessive temperatures.

REFERENCES & PACKING

36871	12 x 1L
36873	3 x 5L
36878	20L
36874	60L
36877	205L